Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

SAMSUNG SECRET

SAMSUNG ELECTRONICS

Product Information

Customer : Voxson **ISSUED DATE : Mar. 09, 2010**

SAMSUNG TFT-LCD

MODEL : **LTA320HF04**

The Information Described in this Specification is Preliminary and can be changed without prior notice

LCD Business

Samsung Electronics Co . , LTD.

MODEL	LTA320HF04 [Voxson]	Doc. No	06-000-G-100309	Page	1 / 27

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

Contents

SAMSUNG SECRET

General Description ---------- (3)

General Information ---------- (3)

1. Absolute Maximum Ratings ---------- (4)
   1.1 Back Light Unit Absolute Maximum Ratings
   1.2 LED Unit Absolute Maximum Ratings

2. Optical Characteristics ---------- (6)

3. Electrical Characteristics ---------- (9)
   3.1 TFT LCD Module
   3.2 Back Light Unit
   3.3 Inverter Input & Specification

4. Input Terminal Pin Assignment ---------- (12)
   4.1 Input Signal & Power
   4.2 Converter Input Pin Configuration
   4.3 Converter Input Power Sequence
   4.4 LVDS Interface
   4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

5. Interface Timing ---------- (18)
   5.1 Timing Parameters (DE only mode)
   5.2 Timing Diagrams of interface Signal (DE only mode)
   5.3 Power ON/OFF Sequence

6. Outline Dimension ---------- (21)

7. Packing ---------- (23)

8. Marking & Others ---------- (24)

9. General Precaution ---------- (25)
   9.1 Handling
   9.2 Storage
   9.3 Operation
   9.4 Operation Condition Guide
   9.5 Others

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

General Description

Description

LTA320HF04 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a back light unit. The resolution of a 32.0“ is 1920 x 1080 and this model can display up to 16.7 Million colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV

Features

- RoHS compliance (Pb-free)
- High contrast ratio & aperture ratio with wide color gamut
- SPVA(Super Patterned Vertical Align) mode
- Wide viewing angle (± 178°)
- FHD resolution (16:9)
- Low Power consumption
- Edge Type LED (Light Emitted Diode) BLU
- DE (Data Enable) mode
- 2ch LVDS (Low Voltage Differential Signaling) interface (2pixel/clock)

General Information

Items	Specification	Unit	Note
Module Size	755.6(H_{TYP}) x 455.4(V_{TYP})	mm	± 1.0mm
	31.2(D_{MAX})		
Weight	8400(Max.)	g	
Pixel Pitch	0.36375(H) x 0.36375(W)	mm	
Active Display Area	698.4(H) X 392.85(V)	mm	
Surface Treatment	Anti-glare		
Display Colors	8 bit – 16.7 M	colors	
Number of Pixels	1920 x 1080	pixel	
Pixel Arrangement	RGB vertical stripe		
Display Mode	Normally Black		
Luminance of White	450 (Typ.)	cd/m^2	

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

1.1 Back Light Unit Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{DD}	GND-0.5	13.2	V	(1)
Storage temperature	T_{STG}	-20	60	℃	(2)
Operating temperature	T_{OPR}	0	50	℃	
Surface temperature	T_{SUR}	0	60	℃	(3)
Shock (non - operating)	X,Y,Z	-	50	G	(4)
Vibration (non - operating)	V_{NOP}	-	1.5	G	(5)

Note (1) Ta= 25 ± 2 ℃
(2) Temperature and relative humidity range are shown in the figure below.
a. 90 % RH Max. (Ta ≤ 39 ℃)
b. Relative Humidity is 90% or less. (Ta > 39 ℃)
c. No condensation
(3) Although abnormal visual problems can be occurred in T_{SUR} range, the polarizer is not damaged in this range.
(4) 11ms, sine wave, one time for ± X, ± Y, ± Z axis
(5) 10-300 Hz, Sweep rate 10min, 30min for X,Y,Z axis



Fig. Temperature and Relative humidity range

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

1.2 LED Unit Absolute Maximum Ratings

Item	Symbol	Max.	Unit	Note
Operating Temperature Range	T_{op}	*-20~+70*	℃	-
Storage Temperature Range	T_{STG}	*-30~+70*	℃	-
Junction Temperature	T_j	110	℃	-
Forward Current	I_f	0.15	A	Continuous operation @ 1Bar
	I_{fp}	0.2	A	Duty 35% operation @ 1Bar
Forward Voltage	V_f	140	V	Continuous operation @ 1Bar
	V_{fp}	151	V	Impulsive operation @ 1Bar
Thermal Resistance, Junction to PCB	$R_{th,JS}$	<45K/W	K/W	-

www.panelook.com

One-stop solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

2. Optical Characteristics

The optical characteristics should be measured in a dark room or equivalent.
Measuring equipment : TOPCON RD-80S, TOPCON SR-3, ELDIM EZ-Contrast

(Ta = 25 ± 2℃, VDD=12V, fv= 120Hz, f_{DCLK} = 297.0MHz, LED Current = 95mA)

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio (Center of screen)		C/R		TBD	5000	-		(1) SR-3
Response Time	G-to-G	Tg	Normal qL,R =0 qU,D =0 Viewing Angle	-	6	-	msec	(3) RD-80S
Luminance of White (Center of screen)		Y_L		TBD	450	-	cd/m²	(4) SR-3
Color Chromaticity (CIE 1931)	Red	Rx		TYP. -0.03	TBD	TYP. +0.03		(5),(6) SR-3
		Ry			TBD			
	Green	Gx			TBD			
		Gy			TBD			
	Blue	Bx			TBD			
		By			TBD			
	White	Wx			0.280			
		Wy			0.290			
Color Gamut		-		-	74	-	%	(5) SR-3
Color Temperature		-		-	10,000	-	K	
Viewing Angle	Hor.	q_L	C/R≥10	79	89	-	Degree	(6) EZ-Contrast
		q_R		79	89	-		
	Ver.	q_U		79	89	-		
		q_D		79	89	-		
White Brightness Uniformity (9 Points)		B_{uni}		-	-	25	%	(2) SR-3

- Test Equipment Setup

The measurement should be executed in a stable, windless and dark room between 40min and 60min after lighting the back light at the given temperature for stabilization of the back light. This should be measured in the center of screen.

. LED current = 95mA
. Environment condition : Ta = 25 ± 2 ℃

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

Photo detector	Field
SR-3	2°
RD-80S	1°



- Definition of test point



Note (1) Definition of Contrast Ratio (C/R)
: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G\max}{G\min}$$

Gmax : Luminance with all pixels white
Gmin : Luminance with all pixels black

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

Note (2) Definition of 9 points brightness uniformity (Test pattern : Full White)

$$Buni = 100 * \frac{(B\max - B\min)}{B\max}$$

Bmax : Maximum brightness
Bmin : Minimum brightness

Note (3) Definition of Response time : Sum of Tr, Tf



Note (4) Definition of Luminance of White : Luminance of white at center point ⑤

Note (5) Definition of Color Chromaticity (CIE 1931)
Color coordinate of Red, Green, Blue & White at center point ⑤

Note (6) Definition of Viewing Angle
: Viewing angle range (C/R ⩾10)



One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

3. Electrical Characteristics

3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

Ta = 25℃ ± 2 ℃

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		V_{DD}	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	I_{DD}	-	700	TBD	mA	(2),(3)
	(b) White		-	700	TBD	mA	
	(c) N-pattern		-	1000	TBD	mA	
Vsync Frequency		f_V	TBD	120.0	TBD	Hz	
Hsync Frequency		f_H	TBD	135.0	TBD	kHz	
Main Frequency		f_{DCLK}	TBD	297.0	TBD	MHz	
Rush Current		I_{RUSH}	-	-	(7)	A	(4)

Note (1) The ripple voltage should be controlled under 10% of V_{DD}.
(2) fV=120Hz, fDCLK = 297.0MHz, V_{DD} = 12.0V, DC Current.
(3) Power dissipation check pattern (LCD Module only)

a) Black Pattern b) White Pattern c) N-pattern



(4) Measurement Conditions



Rush Current I_{RUSH} can be measured when T_{RUSH}. is 470㎲.

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

3.2 Back Light Unit

The back light unit contains Edge type White LEDs (Light Emitting Diode)

Ta=25 ± 2℃



Item	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Life Time	Hr	TBD	-	-	Hour	(1)

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value.

[Operating condition : Ta = 25± 2℃, For single lamp only.]

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

3.3 Inverter Input Condition & Specification

Items	Symbol	Conditions	Specifications			Unit	Note
			Min.	Typ.	Max.		
Input Voltage	Vin	-	22	24	26	V	Ta=25± 2 ℃ (2)
Input Current	I_{RUSH}	Vin=24.0V Vdim =3.3V	-	-	3.43	A	(1)
Lamp Current	$I_{O,MAX}$	Vdim =3.3 V	TBD	95	TBD	mArms	
Frequency	F_{LAMP}	Vin=24.0 V	TBD	TBD	TBD	kHz	-
Backlight On/Off	ON	Vin=24.0 V	2.4	-	5.5	V	(2)
	OFF	Vin=24.0 V	0	-	0.8		
Dimming Control	V_{DIM}	Max Lum	3.3	-	-	V	(2)
		Min. Lum	-	-	0		

Note) Power Consumption is measured when 450 [cd/m] of luminance which is the typical luminance.
Lamp Current is measured at the point before Lamp.

(1) Max Value of the Power Consumption is measured after 60 min warm-up.
(2) The ripple voltage should be controlled under 10% of Input Signal

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

4. Input Terminal Pin Assignment

SAMSUNG SECRET

4.1.1 Input Signal & Power

Connector : FI-RE41S-HF (JAE/UJU)

Pin	Description		Pin	Symbol	Description
1	Vdd(12V)		21	ODD LVDS SIGNAL	Rx1[3]P
2	Vdd(12V)		22		Rx1[4]N
3	Vdd(12V)		23		Rx1[4]P
4	Vdd(12V)		24		GND
5	Vdd(12V)		25		Rx3[0]N
6	No Connection		26		Rx3[0]P
7	GND		27		Rx3[1]N
8	GND		28		Rx3[1]P
9	GND		29		Rx3[2]N
10	ODD LVDS SIGNAL	Rx1[0]N	30		Rx3[2]P
11		Rx1[0]P	31		GND
12		Rx1[1]N	32		Rx3CLK-
13		Rx1[1]P	33		Rx3CLK+
14		Rx1[2]N	34		GND
15		Rx1[2]P	35		Rx3[3]N
16		GND	36		Rx3[3]P
17		Rx1CLK-	37		Rx3[4]N
18		Rx1CLK+	38		Rx3[4]P
19		GND	39	GND	
20		Rx1[3]N	40	No Connection	
			41	No Connection	

Note) No Connection: This PINS are only used for SAMSUNG internal using.

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

4.1.2 Input Signal & Power

Connector : FI-RE51S-HF (JAE/UJU)

Pin	Description		Pin	Description	
1	Vdd(12V)		26	EVEN LVDS SIGNAL	Rx4[0]P
2	Vdd(12V)		27		Rx4[1]N
3	Vdd(12V)		28		Rx4[1]P
4	Vdd(12V)		29		Rx4[2]N
5	Vdd(12V)		30		Rx4[2]P
6	No Connection		31		GND
7	GND		32		Rx4CLK-
8	GND		33		Rx4CLK+
9	GND		34		GND
10	EVEN LVDS SIGNAL	Rx2[0]N	35		Rx4[3]N
11		Rx2[0]P	36		Rx4[3]P
12		Rx2[1]N	37		Rx4[4]N
13		Rx2[1]P	38		Rx4[4]P
14		Rx2[2]N	39	GND	
15		Rx2[2]P	40	No Connection	
16		GND	41	No Connection	
17		Rx2CLK-	42	No Connection	
18		Rx2CLK+	43	No Connection	
19		GND	44	No Connection	
20		Rx2[3]N	45	LVDS Option * Note(1)	
21		Rx2[3]P	46	No Connection	
22		Rx2[4]N	47	No Connection	
23		Rx2[4]P	48	No Connection	
24		GND	49	No Connection	
25		Rx4[0]N	50	No Connection	
			51	No Connection	

NOTE) No connection : This Pins are only used for SAMSUNG internal using

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

Note) Pin number starts from Right side



Fig. Connector diagram

a. All GND pins should be connected together and also be connected to the LCD's metal chassis.
b. All power input pins should be connected together.
c. All NC pins should be separated from other signal or power.

Note(1) LVDS OPTION : If this PIN HIGH (3.3V) → Normal LVDS format
LOW (GND) → JEIDA LVDS format
SEQUENCE : On = VDD(T1) → LVDS Option → Interface Signal(T2)
OFF = Interface Signal(T3) → LVDS Option → VDD



LVDS Option Sequence

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

4.2. Inverter Input Pin Configuration

Connector : Yeon-ho, 20022WR-14B1

Pin No.	Pin Configuration(FUNCTION)
	Master
1	24 V
2	24 V
3	24 V
4	24 V
5	24 V
6	GND
7	GND
8	GND
9	GND
10	GND
11	No Connection
12	Backlight On /Off [ON:2.4 – 5.25 V, OFF: 0 - 0.8 V]
13	Internal Dimming Control [0V:Min, 3.3V:Max]
14	No Connection

4.3. Inverter Input Power Sequence



Note) SEQUENCE : ON = Vin(24V) > Dimming Control ≥ Backlight On/Off
OFF = Backlight On/Off ≥ Dimming Control > Vin(24V)

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

4.4 LVDS Interface

- LVDS Receiver : Tcon (merged)
- Data Format (JEIDA & Normal)

	LVDS pin	JEIDA -DATA	Normal -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R4	R0
	TxIN/RxOUT1	R5	R1
	TxIN/RxOUT2	R6	R2
	TxIN/RxOUT3	R7	R3
	TxIN/RxOUT4	R8	R4
	TxIN/RxOUT6	R9	R5
	TxIN/RxOUT7	G4	G0
TxOUT/RxIN1	TxIN/RxOUT8	G5	G1
	TxIN/RxOUT9	G6	G2
	TxIN/RxOUT12	G7	G3
	TxIN/RxOUT13	G8	G4
	TxIN/RxOUT14	G9	G5
	TxIN/RxOUT15	B4	B0
	TxIN/RxOUT18	B5	B1
TxOUT/RxIN2	TxIN/RxOUT19	B6	B2
	TxIN/RxOUT20	B7	B3
	TxIN/RxOUT21	B8	B4
	TxIN/RxOUT22	B9	B5
	TxIN/RxOUT24	HSYNC	HSYNC
	TxIN/RxOUT25	VSYNC	VSYNC
	TxIN/RxOUT26	DEN	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R2	R6
	TxIN/RxOUT5	R3	R7
	TxIN/RxOUT10	G2	G6
	TxIN/RxOUT11	G3	G7
	TxIN/RxOUT16	B2	B6
	TxIN/RxOUT17	B3	B7
	TxIN/RxOUT23	RESERVED	RESERVED
TxOUT/RxIN4	TxIN/RxOUT28	R0	R8
	TxIN/RxOUT29	R1	R9
	TxIN/RxOUT30	G0	G8
	TxIN/RxOUT31	G1	G9
	TxIN/RxOUT32	B0	B8
	TxIN/RxOUT33	B1	B9
	TxIN/RxOUT34	RESERVED	RESERVED

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	DATA SIGNAL																													GRAY SCALE LEVEL
		RED										GREEN										BLUE										
		R0	R1	R2	R3	R4	R5	R6	R7	R8	R9	G0	G1	G2	G3	G4	G5	G6	G7	G8	G9	B0	B1	B2	B3	B4	B5	B6	B7	B8	B9	
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~ R1020
	↓ LIGHT	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
		1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1021
		0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1022
	RED	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1023
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1
		0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~ G1020
	↓ LIGHT	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
		0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1021
		0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1022
	GREEN	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	G1023
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	B1
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	B2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~ B1020
	↓ LIGHT	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	1	B1021
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	B1022
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	B1023

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

5. Interface Timing

5.1 Timing Parameters (DE mode)

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	TBD	297.0	TBD	MHz	-
Hsync		F_H	TBD	135.0	TBD	KHz	-
Vsync		F_V	TBD	120.0	TBD	Hz	-
Vertical Display Term	Active Display Period	T_{VD}	-	1080	-	Lines	-
	Vertical Total	T_V	TBD	1125	TBD	Lines	-
Horizontal Display Term	Active Display Period	T_{HD}	-	1920	-	Clocks	-
	Horizontal Total	T_H	TBD	2200	TBD	clocks	-

Note) This product is DE mode. But the Hsync & Vsync signal must be inputted

(1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system
(2) Internal VDD = 3.3V

One stop solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

5.2 Timing diagrams of interface signal (DE mode)



One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

5.3 Power ON/OFF Sequence

To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.



T1 : V_{DD} rising time from 10% to 90%
T2 : The time from V_{DD} to valid data at power ON.
T3 : The time from valid data off to V_{DD} off at power Off.
T4 : V_{DD} off time for Windows restart
T5 : The time from valid data to B/L enable at power ON.
T6 : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same as the definition of V_{DD}.
- Apply the lamp voltage within the LCD operation range. When the back light turns on before the LCD operation or the LCD turns off before the back light turns off, the display may momentarily show abnormal screen.
- In case of V_{DD} = off level, please keep the level of input signals low or keep a high impedance.
- T4 should be measured after the Module has been fully discharged between power off and on period.
- Interface signal should not be kept at high impedance when the power is on.
- In Case T5 is less than 1000msec and T6 is less than 100msec, Garbage Display can be seen. (It is not related to electrical function issue, Just for recommendation to prevent Garbage Display)

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

6. Outline Dimension- Front

TBD

www.panelook.com

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

6. Outline Dimension- Rear

TBD

www.panelook.com

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

7. PACKING

7.1 CARTON (Internal Package)

(1) Packing Form

Corrugated fiberboard box and corrugated cardboard as shock absorber

(2) Packing Method



7.2 Packing Specification

Item	Specification	Remark
LCD Packing	36ea / (Packing-Pallet Box)	1. 295.2 kg / LCD (36ea) 2. 12.4 kg / Cushion-pallet (4ea) 3. 4.7 kg / Packing-Pallet Box (1ea) 4. Cushion-pallet Material : EPS 5. Packing-Pallet Box Material : SW
Pallet	1Box / Pallet	1. Pallet weight = 5.7 kg
Packing Direction	Vertical	
Total Pallet Size	H x V x height	1150mm(H) x 985mm(V) x 1149mm(height)
Total Pallet Weight	318 kg	Pallet(5.7kg) + Module (295.2 kg) + Cushion (up + bottom =12.4kg) + Pallet-BOX(4.7kg)

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

8. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

(1) Part number : LTA320HF04
(2) Revision: Three letters
(3) Lot number : X X X X XXX XX X



(4) Nameplate Indication



(5) Packing box attach



(6) Others

1. After service part
   Lamps cannot be replaced because of the narrow bezel structure.

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

9. General Precautions

9.1 Handling

(a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.

(b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.

(c) Refrain from strong mechanical shock and / or any force to the Module. In addition to damage, this may cause improper operation or damage to the Module and CCFT back light.

(d) Note that polarizers are very fragile and could be damage easily. Do not press or scratch the surface harder than a HB pencil lead.

(e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.

(f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.

(g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.

(h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.

(i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or semiconductor would be damaged.

(j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.

(k) Do not disassemble the Module.

(l) Do not disassemble shield case of inverter & LVDS board

(m) Do not connect N.C pins. (Samsung internal use only)

(n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handling a module

(o) Pins of I/F connector should not be touched directly with bare hands.

One-stop solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

9.2 Storage

(a) Do not leave the Module in high temperature, and high humidity for a long time. It is highly recommended to store the Module with temperature from 0 to 35℃ and relative humidity of less than 70%.

(b) Do not store the TFT-LCD Module in direct sunlight.

(c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.

9.3 Operation

(a) Do not connect or disconnect the Module in the "Power On" condition.

(b) Power supply should always be turned on/off by the "Power on/off sequence"

(c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

(d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of lamp(CCFT) and may require higher startup voltage(Vs).

9.4 Operation Condition Guide

(a) The LCD product should be operated under normal conditions.
Normal condition is defined as below;
- Temperature : 20± 15℃
- Humidity : 55± 20%
- Display pattern : continually changing pattern (Not stationary)

(b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc.., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292

Global LCD Panel Exchange Center www.panelook.com 屏库:全球液晶屏交易中心

9.5 Others

(a) Ultra-violet ray filter is necessary for outdoor operation.

(b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.

(c) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on)
Otherwise the Module may be damaged.

(d) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen.
To avoid image sticking, it is recommended to use a screen saver.

(e) This Module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.

(f) Please contact SEC in advance when you display the same pattern for a long time.

One step solution for LCD / PDP / OLED panel application: Datasheet, inventory and accessory! www.panelook.com
605621268124292